

Zwakke Vulstof (Keerkring I)

Datum	Nummer	Zeefdoorval			Bitumen- getal	Holle ruimte %(V/V)	Dicht - heid (Mg/m³)	Oplosbaar- heid water %(m/m)	Massa- verlies %(m/m)	Calcium- carbonaat (%)	aanwezigheid sterk zwellende kleimineralen (g/kg)	Water ge - voeligheid % (m/m)
		2 mm %(m/m)	0,125 mm %(m/m)	0,063 mm %(m/m)								
03.02.2025	02-00039	100	97	87	45	31	2,71	1,6	0,2	70,0	15	KiWa
18.02.2025	02-00611	100	97	87	43	31			0,4	70,7		
25.02.2025	02-00874	100	98	88	44	31			0,2	72,3		
27.02.2025	02-00996	100	98	88	44				0,3	72,1		
28.02.2025	02-01040	100	98	88	44					72,2		

Evaluatie

Rantal van de repeteren	5	5	5	5	3	1	1	4	5	1	1
Minimal Waarde	100	97	87	43	31	2,71	1,6	0,2	70,0	15,0	0
Maximaal Waarde	100	98	88	45	31	2,71	1,6	0,4	72,3	15,0	0
Gemiddelde Waarde	100	98	88	44	31	2,71	1,6	0,3	71,5	15,0	#DIV/0!

Evaluatie

Zwakke Vulstof (Keerkring I)

	2 mm % (m/m)	Zeefdoorval 0,125 mm % (m/m)	0,063 mm % (m/m)	Bitumen- getal	Holle Ruimte % (V/V)	Dicht - heid (kg/m ³)	Oplosbaar- heid water % (m/m)	Massa verlies % (m/m)	Calcium- carbonaat %	aanwezigheid sterk zwellende kleimineralen (g/kg)	Waterge - voeligheid % (m/m)
Minimal Waarde	100	97	87	43	31	2,71	2	0,2	70,0	15	-
Maximal Waarde	100	98	88	45	31	2,71	2	0,4	72,3	15	-
Gemiddelde Waarde	100	98	88	44	31	2,71	2	0,3	71,5	15	-
								-			-
Specificaties minimal	100	90	84	40	30	2,65	-	-	60,0	-	-
Specificaties maximal	-	100	94	46	34	2,75	10	1,0	-	25,0	10
		*	*	*	*						

*) 90% van de resultaten valt binnen deze opgegeven waarden

Blootstellingsindex BI: 10.03.2025	0,0221
---	---------------